



## Immersion temperature sensor

for HVAC systems

**FT-TP/100**  
**FT-TP/400**

---

**Immersion temperature sensor for heating, ventilation and air conditioning systems**

- For use with controllers with Pt100 sensor inputs
- In conjunction with MULTIREG and INTEGRAL RS.

### Use

---

The FT-TP/... immersion temperature sensors can be used in pipe systems for HVAC systems. They are suitable for high accuracy temperature measurement over a wide range with controllers equipped with a Pt100 sensor input, e.g. controllers from the MULTIREG and INTEGRAL RS ranges.

### Type summary

---

2 types are available, distinguished only by the length of the probe.

<b>FT-TP/100</b>	Immersion temperature sensor length 100 mm
<b>FT-TP/400</b>	Immersion temperature sensor length 400 mm

## Ordering

---

When placing an order, please specify the quantity, product description and type code.

Example:

**1 immersion temperature sensor FT-TP/400**

## Technical design

---

The Pt100 temperature sensor is fitted with a platinum measuring element with a positive temperature coefficient (PTC). The measured-signal/temperature relationship is linear. See data sheet 1714 for technical information on the Pt100 sensor element.



The sensor FT-TP/... comprises a probe with a connecting head and the inserted Pt100 element. To improve the response time, the end of the sensor probe is narrowed. The cable is connected via a PG16 cable gland.

## Mounting notes

---

Mounting instructions are enclosed with the sensor (Ref. 35224)

Where possible the immersion sensor should be mounted in a pipe bend with the sensor probe against the direction of flow. It should be located in a position where the medium is well mixed.



## Disposal

---



The device is considered electrical and electronic equipment for disposal in terms of the applicable European Directive and may not be disposed of as domestic garbage.

- Dispose of the device via the channels provided for this purpose.
- Comply with all local and currently applicable laws and regulations.



## Technical data

Measuring range	- 100 ... + 450 °C
Measuring element	Pt100 to IEC751, Class B
Response time (0.632 value time)	to VDI/VDE 3522
in air moving at 1 m/s	<100 s
in water moving at 0.4 m/s	< 5 s
Nominal pressure	PN 40
Suitable media	Gas or liquid
Material	Cast aluminium
Probe	Stainless steel V4A (1.4571)
Electrical connection	2 screw terminals for max. 2.5 mm <sup>2</sup>
Cable gland	PG16
Temperature range	Max. temperature at connecting head 100 °C
EU conformity (CE)	A5W00040799 *)
Protection degree of housing	IP54 according to EN 60529
Protection class	III according to EN 60730-1
Weight (incl. packaging)	FT-TP/100 = 0.47 kg / FT-TP/400 = 0.54 kg
Connecting head	Shape B to DIN 43729
Sensor probe	
Immersed length	FT-TP/100 = 100 mm / FT-TP/400 = 400 mm
Probe diameter	6 mm
Narrowed end	Length 30 mm, diameter 5 mm
Wall thickness	Approx. 0.5 mm
Screw thread	G1/2 to ISO228/1


\*) The documents can be downloaded from <http://siemens.com/bt/download>.

## Connection diagrams

### Four-wire connections




### Two-wire connections



## Dimensions

all dimensions in mm



Published by:  
Siemens Switzerland Ltd.  
Building Technologies Division  
International Headquarters  
Gubelstrasse 22  
6301 Zug  
Switzerland  
Tel. +41 58-724 24 24  
[www.siemens.com/buildingtechnologies](http://www.siemens.com/buildingtechnologies)

© Siemens Switzerland Ltd 2001  
Delivery and technical specifications subject to change